

LED Ring Light

RL12-18s G

100-007694



- Solid aluminium housing in modern design
- Flicker-free lighting thanks to optimized electronic
- Brightness adjustable from 0 to 100%
- Huge illuminance
- Ideal for industry and machine vision
- Homogeneous illumination in the entire working range
- Variable clamping diameter, adaptable with reducing rings
- Various light colors and color temperatures available

| Technical Data | |
|--------------------------|---|
| Working distance | 90 mm - 180 mm |
| Optimum working distance | approx. 140 mm |
| Light color | green (528 nm) |
| Number of LED | 12 × Power-LED (Spot) |
| LED life span | 50.000 h (according to manufacturer) |
| Height | 42 mm |
| Outer diameter | 130 mm |
| Inner diameter | 66 mm |
| Clamping diameter | max. 66 mm |
| Inner thread | M67 × 0,75 |
| Material | anodized aluminium |
| Color | titanium and black |
| Weight Ring Light | approx. 750 g |

| Technical Data | |
|---------------------------------|----------------------------|
| Input power supply | 100 - 240 V AC, 50 - 60 Hz |
| Output power supply | 24 V DC, 1 A |
| Power consumption | approx. 15 W |
| Dimensions control unit (l×w×h) | 78 mm × 38 mm × 21 mm |

Accessories

- Diffusor and protection glasses
- Polarisation filter sets
- Various reducing rings
- Extensions for connector cables

**MADE
IN
GERMANY**

